



Early Journal Content on JSTOR, Free to Anyone in the World

This article is one of nearly 500,000 scholarly works digitized and made freely available to everyone in the world by JSTOR.

Known as the Early Journal Content, this set of works include research articles, news, letters, and other writings published in more than 200 of the oldest leading academic journals. The works date from the mid-seventeenth to the early twentieth centuries.

We encourage people to read and share the Early Journal Content openly and to tell others that this resource exists. People may post this content online or redistribute in any way for non-commercial purposes.

Read more about Early Journal Content at <http://about.jstor.org/participate-jstor/individuals/early-journal-content>.

JSTOR is a digital library of academic journals, books, and primary source objects. JSTOR helps people discover, use, and build upon a wide range of content through a powerful research and teaching platform, and preserves this content for future generations. JSTOR is part of ITHAKA, a not-for-profit organization that also includes Ithaka S+R and Portico. For more information about JSTOR, please contact support@jstor.org.

5. After May 1, 1914, the ceiling of every cellar stable for which the first application for a permit is made shall not be less than 8 feet from the floor.

6. There shall be not less than 800 cubic feet of air space for each horse.

7. Floors must be of concrete or other approved nonabsorbent material.

8. Floors of horse stalls must be of concrete or other approved nonabsorbent material, graded to a properly graded, trapped, and sewer-connected valley drain. All racks provided shall be removable.

9. Walls, ceilings, exposed woodwork, floors, horse stalls, and valley drains of cellar stables must be maintained in a clean condition at all times, and the whitewashed portions are to be rewhitewashed when necessary.

10. Every cellar stable must be maintained so as not to cause a nuisance.

11. No manure vault shall be allowed upon the premises. The loading of manure for removal must be done inside of stable without causing a nuisance.

Waste, Soil, and Vent Pipes—Extension Above Roof Required. (Reg. Bd. of H., Mar. 31, 1914.)

Resolved, That section 30 of the Sanitary Code be, and is hereby, repealed. Be it further

Resolved, That section 36 of the Sanitary Code be, and the same is hereby, amended so as to read as follows:

SEC. 36. All waste, soil, and vent pipes in any building in the city of New York shall extend above the roof thereof to a height of at least 2 feet, and that portion of the pipe extending above the roof shall be of an increased diameter. All such pipes shall be so constructed and located that they shall not contribute to the creation of a nuisance.

Water Tanks on Buildings to be Cleaned, Screened, and Ventilated. (Reg. Bd. of H., Apr. 21, 1914.)

Resolved, That section 62a of the Sanitary Code be, and the same is hereby, amended so as to read as follows:

SEC. 62a. Every tank for holding water located on the roof or external part of a building shall be kept covered with a tight-fitting cover, or with an extra fine mesh screen to prevent the access of mosquitoes to the water therein; and every such tank shall be ventilated. Every tank from which water is furnished for drinking and domestic purposes shall be emptied and the inside thoroughly cleaned at least once a year and at such other times as may be directed by the sanitary superintendent or an assistant sanitary superintendent of the department of health.

Bathing Beaches and Bathhouses—Location—Sanitary Regulation. (Reg. Bd. of H., Apr. 21, 1914.)

1. No bathing beach shall be maintained within 500 feet of the point of discharge or outlet of any sewer which would contribute in any way to the pollution of the waters used by bathers.

2. An adequate supply of pure drinking water must be provided for patrons. Water from wells in the borough of Manhattan shall not be used for drinking. Water from wells in the other boroughs, other than the public water supply, shall not be used without a permit from the board of health.

3. Life lines and danger signs must be provided in accordance with the provisions of section 26 of the Sanitary Code.